

SIVGE B42 SERIES



Mobile Elevating Work Platforms



Product conform with below standards:

- 2006/42/EC Machinery Directive
- EN 280-2013+A1-2015
- EN ISO 12100: 2010
- EN 60204-1:2006+A1:2009+AC:2010
- EN ISO 13849-1:2015
- GB25949-2010
- JB/T12216-2015

- * Suitable for 1 person to work upraised.
- * Maximum working height available:
16m, 18m, 20m, 22m, 24m



HANGZHOU SIVGE MACHINERY CO.,LTD
ADD: NO 15 KANGXIAN ROAD, GONGSHU DISTRICT,
HANGZHOU, ZHEJIANG, CHINA
POST CODE: 310015 TEL: +86 571 88043728 88043711
FAX: +86 571 88043715 E-mail: info@sivge.com




© www.sivge.com
© www.aerial-workplatform.com
sivge stock(833084)

B42 Series Multi-mast

STANDARD FEATURES:

- Dual controls operation
- Emergency stop buttons at both controls
- Intelligent anti-tilt: The controller checks the slope angle of chassis automatically
- Double emergency lowering devices in case of power supply failure
- Double safety protection with leveling stabilizers and outriggers support
- Forklift pocket
- Traveling method: powered self-propeller

	B4214	B4216	B4218	B4220	B4222
Model-code	GTWB14-4214	GTWB16-4216	GTWB18-4218	GTWB20-4220	GTWB22-4222
Platform height(m)(h ₁)	14	16	18	20	22
Working height(m)(h ₂)	16	18	20	22	24
Capacity(kg)/occupants	200/1	136/1	120/1	120/1	120/1
Platform size(mm)	1480*860	700*700	700*700	700*700	700*700
Outrigger footprint(mm)	3350*3000	4200*3000	4200*3140	4200*3140	4200*3410
Stowed length(mm)(l ₀)	2360	3220	3220	3220	3220
Stowed width(mm)(w ₀)	1250	1250	1390	1660	1660
Stowed height(mm)(h ₀)	1920	2190	2350	2650	2780
Machine weight(kg)	1950	2200	2300	2550	2700
Wheelbase(mm)	1880	2750	2750	2750	2750
Front Tyres	12 inch	10 inch	10 inch	10 inch	10 inch
Back Tyres	12 inch	12 inch	12 inch	12 inch	12 inch
Ground clearance (mm)	55	55	55	55	55
Power supply	Elevating AC220V 1.5/0.75Kw; Driving DC24V 0.8Kw				
Moving methods	DC type walking control				
Steering mode	Wire control rear axle				
Up-down speed	Up 4.6m/min; Down 5.5m/min.				
Travel speed (stowed)	1.4Km/h				
Travel speed (raised)	0				
Max. allowed wind speed	12.5m/s				
Rated oil pressure	12Mpa				
Battery	12V/120Ah*2				
Integrated charger	DC24V/15A with AC220V input input				



Optional:

UPS for elevating 3Kw

※ Optional: design service is available if the standard models cannot fulfill the needs.
□ Product specifications are subject to change without notice or obligation.